

IC-446S

"PRO" grade simplicity and reliability, nothing less

Easy to operate

PMR446 is a new pan-European, radio service. Designed from the outset for ease of use, there are an absolute minimum of switches with easy to understand labels, making operation easy for beginners. The large, easy-to-read LCD shows operating information at a glance with status icons such as "low battery," "timer" and "function lock" easily recognizable. And for low light conditions, there is an auto backlight function.

Automatic transponder function

This convenient function automatically checks station availability with the operating range, and alerts you via function display indication.

PMR446

At a working site...

Other outstanding features

- Compact body— fits neatly in your palm
- Optional Ni-Cd battery and rapid charger are available
- Economical AA (R6)×3 dry or alkaline cells can be used
- Auto power-OFF timer
- Time-out timer function
- Low battery indicator
- Fold-away antenna, and more...

At a sporting event...

At the shopping mall...

'Smart-Ring' function

'Smart-Ring' is used in "Group Mode" operation to check for availability of stations in a specified group within the operating range. When stations are available, the transceiver alerts you audibly.

'Call-Ring' function

'Call-Ring' is used to manually send a ring tone when calling another party—similar to using a cellular phone. Ten different ring types can be selected from.

Water-resistant

Essential for reliable communications in the great outdoors!

Group mode

To reduce interference from other radios, you can select from 8 different radio channels and 38 different group codes, giving more than 300 different combinations!



SPECIFICATIONS

• Number of channels : 8 (simplex; 446.00625–446.09375 MHz)

CH 1	466.00625	CH 5	466.05625
CH 2	446.01875	CH 6	446.06875
CH 3	446.03125	CH 7	446.08125
CH 4	446.04375	CH 8	446.09375


- Mode : FM (8K50F3E)
- Frequency stability : ±2.5 kHz
- Frequency resolution : 12.5 kHz
- Power supply requirements : 3 × AA(R6) dry, alkaline; or optional BP-202
- Current drain : Less than 500 mA
- Operating temp. range : -20°C to +55°C
- Number of CTCSS frequency : 38 (67.0–250.3 Hz)
- Weight (includes 3 cells) : 180 g
- Output power : Less than 500 mW ERP
- External microphone connector : 3-conductor 2.5 (d) mm/2.2 kΩ
- Sensitivity (12 dB SINAD) : Less than 0.25 µV; -12 dBµV
- Audio output power (at 4.5 V DC) : More than 100 mW at 10% distortion with an 8 Ω load
- External SP connector : 2-conductor 3.5 (d) mm/8 Ω
- Battery life (Tx:Rx:Standby=1:1:8) :

Battery type	Battery life
3 alkaline cells	approx. 28 hrs.
Optional BP-202	approx. 10 hrs.

• Communication range* :

Wide, open spaces with good visibility	approx. 3 km
Suburbs	approx. 1–3 km
Highways	approx. 500 m
City areas	approx. 100–200 m

*Communication ranges listed above may differ depending on weather conditions, etc.



All stated specifications are subject to change without notice or obligation.

OPTIONS

BC-119 DESKTOP CHARGER + **AD-89** DESKTOP CHARGER ADAPTER
BC-119L DESKTOP CHARGER SET

BC-119

AD-89

BC-119L

Rapidly charges installed Ni-Cd battery cell assembly, BP-202. Both AC and DC can be used to power the charger. Charging time: 75 to 85 min.

BP-202 Ni-Cd BATTERY CELL ASSEMBLY

Install into the battery cell space in the transceiver.
3.6 V/700 mAh

HS-85 HEADSET

For hands-free operation. Includes VOX, PTT and "one-touch" PTT with a time-out timer.

HM-46 SPEAKER-MICROPHONE

Compact and lightweight. Equipped with an earphone jack and a transmit indicator.

HM-54 SPEAKER-MICROPHONE

Durable, full-sized speaker-microphone.

HM-75A SPEAKER-MICROPHONE

Allows you to remotely select operating channels, etc.

Icom Inc.

1-1-32, Kamiminami, Hirano-ku, Osaka 547-0003, Japan Phone: 06 6793 5302 Fax: 06 6793 0013 URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

<Corporate Headquarters>
2380 116th Avenue N.E., Bellevue, WA 98004, U.S.A.
Phone: (425) 454-8155 Fax: (425) 454-1509
URL : <http://www.icomamerica.com>
<Customer Service> Phone: (425) 454-7619

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone: (604) 952-4266 Fax: (604) 952-0090
URL : <http://www.icomcanada.com>

Icom (Australia) Pty. Ltd.

A.B.N. 88 006 092 575
290-294 Albert Street, Brunswick, Victoria, 3056, Australia
Phone: 03 9387 0666 Fax: 03 9387 0022
URL : <http://www.icom.net.au>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road, Taipei, Taiwan, R.O.C.
Phone: (02) 2559 1899 Fax: (02) 2559 1874

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100, D-40225 Düsseldorf, Germany
Phone: 0211 346047 Fax: 0211 333639
URL : <http://www.icomeurope.com>

Icom Spain S.L.

Crta. de Gracia a Manresa Km. 14,750
08190 Sant Cugat del Valles Barcelona, SPAIN
Phone: (93) 590 26 70 Fax: (93) 589 04 46
URL : <http://www.icomspain.com>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay, Kent, CT6 8LD, U.K.
Phone: 01227 741741 Fax: 01227 741742
URL : <http://www.icomuk.co.uk>

Icom France Sa

Zac de la Plaine, Rue Brindejonc des Moulinais
BP 5804, 31505 Toulouse Cedex, France
Phone: 561 36 03 03 Fax: 561 36 03 00
URL : <http://www.icom-france.com>



Certificate Number Q14190

Icom Inc. (Japan), is an ISO9001 certification acquired company.

Your local distributor/dealer: